

# 爪型干式多级泵

MULTISTAGE CLAW TYPE DRY PUMP

GZ系列爪型干式真空泵采用模块化设计，配件独立更换，运行费用更低。

GZ series claw type dry vacuum pump adopts modular design, independent substitutions of accessories, lower operating costs.



智能  
控制



低碳  
环保



维护  
简单



高效  
节能

## 产品优势 ADVANTAGES

- ◆ 真空度高- 极限真空可达3Pa

High vacuum degree - ultimate vacuum up to 3Pa

- ◆ 防抱死--特有的自动维护技术，防止爪泵抱死故障

Anti-lock - unique automatic maintenance technology to prevent fault locked of claw dry pump

- ◆ 无油无污水-清洁环保，免除污水处理费用

No oil and no sewage - clean and environmental protection, free of sewage treatment fees

- ◆ 专利密封技术-彻底隔绝油箱与真空腔

Patented sealing technology - completely isolate the tank from the vacuum chamber

# 技术指标

## SPECIFICATIONS

型号 MODEL	GZ4	GZ8	GZ15	GZ30	GZ50	GZ70	GZ110	GZ150	GZ200	GZ300	GZ1600
抽速速率L/S PUMPING SPEED	4	8	15	30	50	70	110	150	200	300	1600
极限压强Pa ULTIMATE PRESSURE	≤1000	≤1	≤1	≤1	≤1	≤1	≤1	≤1	≤1	≤1	≤2000
电机功率KW MOTOR POWER	1.1	2.2	3	5.5	7.5	11	15	18.5	22	37	90
电源电压V POWER SUPPLY	220/ 380	220/ 380	380	380	380	380	380	380	380	380	380
冷却方式 COOLING MODE	风冷AIR/ 水冷WATER	水冷 WATER									
噪音dB NOISE	60	65	65	70	70	75	75	75	75	80	100
重量kg WEIGHT	25	60/ 125	70/ 140	350	400	650	700	750	900	1100	7800
入口连接 INLET CONNECTION	KF15	KF15	KF15	KF25	KF25	DN65	DN65	DN80	DN100	DN65	DN65
排口连接 OUTLET CONNECTION	G1/4	G1/4	G1/4	G3/4	G3/4	DN65	DN65	DN65	DN65	DN100	DN200
泵体材料 MATERIAL	复合材料 COMPOSITE MATERIAL	铝/45#钢/不锈钢 ALUMINUM /45# STEEL/STAINLESS STEEL									
外形尺寸(长宽高) OVERALL DIMENSION L×W×H	400* 400* 190	700* 400* 350	780* 400* 350	1100* 450* 350	1200* 450* 350	800* 700* 1300	800* 700* 1400	800* 700* 1500	800* 700* 1550	800* 700* 1550	2900* 1900* 1700

## 可选项 OPTIONAL

过滤器 Filter

消音器 Silencer

可选防腐涂层：镍磷合金/渗透哈氏合金/高分子涂层 Optional anticorrosive coating

智能自清洗 Intelligent self-cleaning

电机：防爆/非防爆 Electric machine: explosion-proof/non-explosion-proof

泵体材料：钢/铝 Pump body material: steel/aluminum

控制方式：手动/自动 Control mode: manual/automatic

显示屏 Display screen

降噪外壳 Noise reduction housing